

# Datasheet

## SMD3528 T8 600MM LED Tube Light

### Features:

1. LED Chip: SMD3528
2. Insulated PC & ABS endcap, Hi-pot proofing
3. Isolated power supply available for freely choice, PFC: >0.9
4. LED Output: 85-95lm/W
5. "D" shape aluminium housing (Diameter: 26\*28mm)  
(O shape also available as required at the same price)
6. Input Voltage: AC170-260V (AC 85-265V also available)
7. Pin type: T8- G13
8. Working Frequency: 50-60Hz
9. Covers: Frosted/Clear/Striped
10. Beam angle: Transparent cover's :120°, Frosted cover's 160
12. Ambient Temperature: -30°C to 55°C
13. Both single-ended and double ended type available
14. Ideal replacements for traditional tubes
15. Instant on, flicker free and noiseless
16. Approval by CE& Rohs
17. With Rotating end cap



Item No.	600mm Specifications				
	Watt Consumption	LED Quatity	Size (L*D)	Wavelength	
CY-T8-3528-S12W60D	12W	168pcs	600(L)*26*28(Dia.)	632-647nm	
<b>1200mm</b>					
CY-T8-3528-S25W120D	25W	360pcs	1200(L)*26*28 (Dia.)	632-647nm	/
<b>1500mm</b>					
CY-T8-3528-S30W150D	30W	420pcs	1500(L)*26*28 (Dia.)	632-647nm	/